

## Industriemonitore Industrial Monitors



### Digitale TFT LCD Bildschirme von 8,4" bis 19"

- 12V Stromversorgung
- Eingänge: AV Composite, VGA, DVI,
- Metallgehäuse
- Automotive Steckverbindungen
- Resistent gegenüber Erschütterungen
- Für Anwendungsbereiche unter Extrembedingungen
- spannungsstabil 11V~16V
- inkl. Fernbedienung (12"-19")
- VESA 75 / 100 kompatibel

### Digital TFT LCDs from 8,4" to 19"

- Power supply 12V
- Inputs: AV Composite, VGA, DVI
- Metal housing
- Automotive Plugs
- Resistant against vibrations
- For application under extreme conditions
- Supports voltage from 11V~ 16V
- Remote control (12"-19")
- compatible with VESA 75 / 100

### Technische Daten Technical Details

Modell	MM-840D	MM-1040D	MM-1210D	MM-1510D	MM-1710D	MM-1910D
Typ	Colour TFT	Colour TFT	Colour TFT	Colour TFT	Colour TFT	Colour TFT
Bildschirmdiagonale / screen size	8,4" / 21,3cm	10,4" / 26,4cm	12" / 30,48cm	15" / 38,1cm	17" / 43,1cm	19" / 48,3cm
Seitenverhältnis / aspect ratio	4:3	4 : 3	4:3	4:3	4:3	4:3
Auflösung / resolution	800 x 600	800 x 600	800 x 600	1024 x 768	1280x1024	1280x1024
Blickwinkel / view angle (L/R/U/D)	55°/55°/35°/35°	55°/55°/35°/35°	56°/56°/37°/37°	80°/80°/80°/70°	75°/75°/75°/60°	80°/80°/80°/80°
Video System	NTSC / PAL / Auto	NTSC / PAL / Auto	NTSC / PAL / Auto	NTSC / PAL / Auto	NTSC / PAL / Auto	NTSC / PAL / Auto
Helligkeit / brightness	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>	300cd/m <sup>2</sup>
Kontrast / contrast	250:1	400:1	500:1	450:1	500:1	600:1
Dimmer	manually	manually	manually	manually	manually	manually
Stromverbrauch / power consumption	10W at 12V	10W at 12V	20W at 12V	30W at 12V	36W at 12V	36W at 12V
Stromversorgung / voltage	11V - 16V	11V - 16V	11V - 16V	11V - 16V	11V - 16V	11V - 16V
Anschlüsse / connectors	1xVideo in 1xS-Video in 1xS-Audio in 1xAudio in 1xVGA in	1xVideo in 1xS-Video in 1xS-Audio in 1xAudio in 1xVGA in	2xVideo in 2xAudio in 1xAudio out 1xVGA in 1xDVI in	2xVideo in 2xAudio in 1xAudio out 1xVGA in 1xDVI in	2xVideo in 2xAudio in 1xAudio out 1xVGA in 1xDVI in	2xVideo in 2xAudio in 1xAudio out 1xVGA in 1xDVI in
Betriebstemperatur / operating temperature	-10° to +50°	-10° to +50°	0° to +50°	0° to +50°	0° to +50°	0° to +50°
Lagertemperatur / storage temperature	-20° to +50°	-20° to +50°	-20° to +70°	-20° to +70°	-20° to +70°	-20° to +70°
Maße / dimensions	215 x 179 x 35 mm	247 X 208 x 35 mm	308 x 238 x 42 mm	356 x 289 x 40,5 mm	389 x 331 x 48 mm	435 x 368 x 49 mm
Gewicht / weight	1400g	1780g	2600g	3600g	5500g	7000g
Zertifikate/ test marks	E11 CE	E11 CE	E11 CE	E11 CE	E11 CE	E11 CE
Zubehör / Accessories	Standfuß, 12V Anschlusskabel, Multikabel / dash top stand, cigar lighter plug, monitor cable ass'y	Standfuß, 12V Anschlusskabel, Multikabel /dash top stand, cigar lighter plug, monitor cable ass'y	12V Anschlusskabel, Multikabel, Fernbedienung / cigar lighter plug, monitor cable ass'y, remote contr.	12V Anschlusskabel, Multikabel, Fernbedienung / cigar lighter plug, monitor cable ass'y, remote contr.	12V Anschlusskabel, Multikabel, Fernbedienung / cigar lighter plug, monitor cable ass'y, remote contr.	12V Anschlusskabel, Multikabel, Fernbedienung / cigar lighter plug, monitor cable ass'y, remote contr.
Artikelnummer	1436M	1437M	1446M	1437DS	1447M	1449M