



Rear View Cameras

Shutter Cameras



EM.000013/30 ControlLaser Shutter Camera RSE-3000C - 145°

High resolution backup camera with motorized shutter to protect the camera glass against dirt and / or damage. A special integrated wiper cleans the glass everytime the shutter opens or closes. Furthermore there is a built-in heater, which automatically turns on at or below 5°. This product is recommended for winter road vehicles, street cleaning vehicles, construction machines and nearly every type of commercial vehicle.

APPLICATIONS



TRANSPORTER



URBAN VEHICLES



SMALL TRUCKS



COMMERCIAL VEHICLES



TRUCKS WITH TRAILER



FIRE FIGHTING VEHICLES



CONSTRUCTION MACHINES



Specifications	
Resolution	1,23 mega pixel
Image sensor	CMOS
Angle of view	145° (diagonal)
Protection class	IP69K
Vibration resistance	10G
Shock resistance	100G
Power supply	12V DC
Power consumption	max. 3W
Operating temperature	-40°C to +85°C
Storage temperature	-30°C to +80°C
Weight	480g
Dimensions (W x D x H)	104 x 55 x 62 mm

Accessory



BX.000038
 Shutter Control Box EMC10S
 Automatic shutter control for standard monitors
 and special vehicle displays