Data Sheet



A1.	Model No.:				A2. Produc	t Name:		
	10409				U U	80P Wireless Camer in Battery and Magn		
31.	Product Keywords:							
1)	1080P High Resolution				Adapter			
2)	Waterproof: IP69K approved					1		
3) '	Working status switch button, swtich b	etween work/sleep mode;	ween work/sleep mode;					
4)	Battery capacity indicator;	-						
5)	Overcharging/Overdischarging protect	n						
6)	Short-circuit protection;							
	verheat and low temperature protection; rong magnetic base							
.,	Vhen monitor enters standby mode for 20s, or switch to other channel, camera will nter standby mode; when monitor goes back to work, camera will be woken up nd work;(When monitor and camera both have Low power module)					0		
0)	Low power consumption :less than 1.5mW at sleep mode; less than 10mW at standby mode.							
	Strong magnetic base Key Specifications:							
	Battery Capacity 3.6V/6400mAh							
	Charging Voltage	DC 5~12V			TIP	5		
	Charging Time	5V/8H,12V/3H		1. To prote	ect the hatt	attery from damage,		
	Charging Current	5V/1.5A(MAX),12V/1.5A(MAX)			5% of capacity		
	Discharging Time	9H (Daytime) 5H(nighttim				for a long period of		
	Charging Temperature	-10 ~ 45℃	•,		er stored for long time, the initial ing current might be relatively low ill become normal after a while.			
	·	-20 ~ 60°C		150 days.				
	Discharging Temperature	-20 ~ 60 ℃ -20 ~ 60°C		2. After sto				
	Storage Temperature							
	Waterproof Rating	IP69K		but will be				
	Dimension	116*80*66 (mm)		2.46.4.4				
	Weight	670 g		AC Adapter(Charger) is r for charging use.		er) is recommended		
	Image Device	1/2.9" CMOS		ior chargi				
	Effective Pixels	1920 (H) x 1080 (V)						
I	Pixel size	4.2um×4.2um						
;	Scanning System	Progressive Scanning	re Scanning					
1	Sync. System	Internal						
4	AGC	Auto						
;	S/N Ratio	38dB						
1	White Balance	Auto						
I	BLC	Auto						
(Operation Frequency:	2403MHz-2478MHz						
I	Receiving Sensitivity:	-78dBm						
,	Video Codec:	H.264						
I	Frame Rate:	25/30fps						
	Transmission Power	FCC: ≤26dBm CE: ≤20dBm MIC: ≤10dBm						
	Transmission Distance	FCC: ≤300m CE: ≤200m MIC: ≤60m						
:	Spread SPECTRUM:	FHSS						
I	Delay:	170ms						
I	RF Bit Rate:	12Mbps						
I	Minimum Illumination	0.1 Lux (day), 0 Lux (with IR)						
I	Power Supply	DC 10~32V						
I	Night vision distance	8~10m						
,	Waterproof rating	IP69K						
,	Viewing Angle	130°						
Vei	ght Of Unit Product:	0.75 KG 0.85 KG (with adapter)	Weigh	t Of Export C	arton:	3.5 KG 4 KG (with adapter)		